

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
19 May 2005 (19.05.2005)

PCT

(10) International Publication Number
WO 2005/045136 A1

(51) International Patent Classification⁷: **E02B 3/06**

(21) International Application Number:
PCT/GB2003/004526

(22) International Filing Date: 21 October 2003 (21.10.2003)

(25) Filing Language: English

(26) Publication Language: English

(71) Applicant and

(72) Inventor: BUDD, Christopher, Anthony [GB/GB]; 4
Blackfield Lane, West Moors, Ferndown, Dorset BH22
0NH (GB).

(74) Agent: BARKER BRETTELL; Medina Chambers, Town
Quay, Southampton SO14 2AQ (GB).

(81) Designated States (national): AE, AG, AL, AM, AT, AU,
AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU,

CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE,
GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR,
KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK,
MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT,
RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR,
TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.


(84) Designated States (regional): ARIPO patent (GH, GM,
KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW),
Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),
European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE,
ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO,
SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM,
GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

— with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: FLOATING BREAKWATER AND PROPULSION SYSTEM



(57) Abstract: The invention, relates to means for absorbing, extracting or using for propulsion, wave energy occurring naturally in water. The invention overcomes existing breakwater devices of the type that were prone to puncture or were expensive to maintain, were inertial dependant or had mooring loads. One breakwater device comprises first and second structures, (100, 102) arranged substantially parallel one to another, said structures having neutral buoyancy and energy absorbers (111) mounted therebetween, whereby in use, the devices absorb energy from incident and waves as a result of relative motion between the structures. Preferably a third structure is positioned parallel to the second structure, there being a second energy absorber positioned between the second and third structures. Energy absorbers may be arranged to generate an electromotive force or pump a material or fluid. Advantageously a plurality of devices (206) can be interconnected, in the form of a chain or caterpillar to provide a breakwater system. Alternative embodiments of the invention include means to alleviate high side loads on multi-hulled vessels, and a propulsion device in which the first and second structures incorporate louver valve assemblies.

WO 2005/045136 A1